

LA-UR-13-24825

Approved for public release; distribution is unlimited.

Title: Applications of laser-driven ion beams

Author(s): Fernandez, Juan C.

Intended for: International Conference on High Energy Density Physics (ICHED) 2013,
2013-06-25/2013-06-28 (Saint Malo, France)

Issued: 2013-07-01



Disclaimer:

Los Alamos National Laboratory, an affirmative action/equal opportunity employer, is operated by the Los Alamos National Security, LLC for the National Nuclear Security Administration of the U.S. Department of Energy under contract DE-AC52-06NA25396. By approving this article, the publisher recognizes that the U.S. Government retains nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or to allow others to do so, for U.S. Government purposes. Los Alamos National Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Department of Energy. Los Alamos National Laboratory strongly supports academic freedom and a researcher's right to publish; as an institution, however, the Laboratory does not endorse the viewpoint of a publication or guarantee its technical correctness.

Applications of laser-driven ion beams

presented by:

Juan C. Fernández

Los Alamos National Laboratory

contributions from:

LANL & Collaborating
Institutions








(Acknowledgements
throughout the talk)

presented to:

2013 ICHED

Saint Malo, France

June 23-28, 2013



Acknowledgements:

- LANL
 - **B. J. Albright, A. Favalli**, D. C. Gautier, K. Falk, A. Favalli J. C. Fernández, N. Guler, B. M. Hegelich*, **C. Huang**, D. Jung¹, S. Letzring, S. Palaniyappan, R. Shah, L. Yin, C. Wilde & H. Wu² and others
- Univ. Politécnica de Madrid
 - J. Javier Honrubia
- Ludwig Maximilian Univ.
 - D. Habs, D. Kiefer, V. Liechtenstein, J. Schrieber
- Technical Univ. Darmstadt.
 - **M. Roth**



Funding:

- Trident operations: LANL ICF and Weapons Science Campaigns
- Project: LANL LDRD program, HEDLP Joint DOE-NNSA program

* Now at Physics Dept., Univ. Texas, Austin

¹ Now at Queen's Univ., Belfast

² Now at Zhejiang University, Hangzhou, China



UNCLASSIFIED


Slide 2



Outline


- Physics of ion acceleration
 - Mechanisms
- Applications
 - Neutron generation
 - Mix across sharp interfaces with heterogeneous species
 - Ion-fast ignition
- Summary

Ion Accel.




Neutrons

Mix



Ion FI



Taxonomy of ion acceleration mechanisms:





Laser-driven ion acceleration mechanisms		Laser-plasma regime	
		Opaque	Relativistically Transparent
Laser target morphology	Thick (micro) foils, solid density	TNSA	
	Thin (nano) foils, solid density	RPA-LS, LICPA	BOA, ISWA
	Near critical-density, long plasmas	RPA-HB, CESA, MVA	

Glossary of laser-driven ion acceleration mechanisms	
BOA	Break-Out Afterburner
ISWA	Ion Solitary Wave Acceleration
RPA-LS	Radiation Pressure Acceleration, Light-Sail Regime
RPA-HB	Radiation Pressure Acceleration, Hole-Boring Regime
CESA	Collisionless Electrostatic Shock Acceleration
MVA	Magnetic Vortex Acceleration
LICPA	Laser Induced Cavity Pressure Acceleration
TNSA	Target Normal Sheath Acceleration

Several *distinct* ion acceleration mechanisms

Thin foils, initially **solid-density** plasmas:

- Radiation Pressure Acceleration, light-sail regime (RPA-LS)*
 - Requires **opaque** plasma, clean charge separation (negligible heating, Circ. Pol.)
- Ion Solitary Wave Acceleration (ISWA)¹
 - Charge Sep. → Soliton → RIT → ISWA
- Breakout afterburner (BOA)²
 - RIT → Electron-ion drift → wave → BOA





Thick (10's μm), near n_{cr} density, opaque plasmas:


- RP – Hole Boring Regime (RPA-HB)³
- Collisionless Electrostatic Shock Acceleration (CESA)⁴

Thick, solid-density opaque foils:

- Target normal sheath acceleration (TNSA)⁵
 - Maxwellian ion energy distribution




* A Macchi *et al* 2010 New J. Phys. **12** 045013; ¹D Jung *et al* 2011 PRL **107** 115002; ²L. Yin *et al* 2007 PoP **14** 056006; B Albright *et al* 2007 **14** 094502; ³T Schlegel *et al* 2009 PoP **16** 083103; ⁴J Denavit 1992 PRL **69**, 3052; ⁵S Hatchett *et al* 2000 PoP **7** 2076




$$\delta_e = \sqrt{\frac{c^2 m_e \gamma}{4 \pi e^2 n_e}}$$

$$\omega_{pe} < \omega_0$$






BOA dependence on thickness: really an optimization of relativistic transparency with with laser pulse length.

- Trident experiments
- Targets: Diamond uncleaned



BOA → TNSA

D. Jung, *et al.*, 2013
 NJP 15 023007




BOA → TNSA

Ion acceleration mechanism cannot always be ascertained from limited data scaling alone.

- Consider Trident experiments
 - Linear polarization (vigorous electron heating)
 - BOA mechanism
 - Verified relativistic induced transparency (R. Shah, ICHED, Tues)
- Ion energy from target thickness l in RPA is

$$E_{ki} = A m_p c^2 \xi^2 / 2[\xi+1] \text{ where } \xi = 2 I_L t_L / \rho l c^2$$
- In strongly relativistic regime
 $\xi \gg 1$ (where we're *not*),


$$E_{ki} \sim a_0^2 t_L / l$$
- BOA data above optimum thickness mimics relativistic RPA scaling**
- Shows importance of full exploration of phase space (simulations and Exps)



Selected applications enabled by laser-driven ion beams


1. Laser-driven neutron beams

- HED-target probe
- Active interrogation
- Materials science





2. Evolution of high-Z or solid particulates in low-Z plasmas

- Coulomb explosion
- Mix



3. Ion-driven FI


- Laser-driven proton or ion beam ignitor of compressed DT fuel



Selected applications enabled by laser-driven ion beams


1. Laser-driven neutron beams

- HED-target probe
- Active interrogation
- Materials science





2. Evolution of high-Z or solid particulates in low-Z plasmas

- Coulomb explosion
- Mix




3. Ion-driven FI

- Laser-driven proton or ion beam ignitor of compressed DT fuel




Record neutron production with Trident laser-produced deuterium beam using BOA*

neutrons



- Driven by D beam (BOA mechanism)
- Neutron source ~ ns, forward-directed (~ 0.25 - 1 Srad)
- f/3 laser: record laser-produced yield (~ 10⁹ neutrons) & forward fluence (~ 5 × 10⁹ n/strad = 50 neutrons/μm² @ 1 cm), 5-15 MeV neutron energies (~ 10 MeV peak)*
- f/1.5 (~ 1.2×10²¹ W/cm²): × 10 higher yield and forward fluence, peak energy to ~ 70 MeV, cutoff to ~ 150 MeV*



*M. Roth et al., PRL **110**, 044802 (2013); D. Jung *et al.*, accepted to PoP (2013), highlighted by APS, Nature and Physics World


Laser-based neutron source shown on Trident has demonstrated utility for active interrogation*

neutrons


- Fission signatures for nuclear materials:
 - + Delayed and prompt fission neutrons,
 - + Delayed and prompt fission γ 's
- Detectors
 - + Bubble & He-3 detectors (insensitive to γ 's)
 - + TOF (γ flash & neutrons)
- Converters: Be (mm's from target), Cu (far)
- Application **results** so far:
 - + **Detected DU** with delayed fission neutrons with Be converter (more efficient but farther from sample)
 - + **Detected DU** with delayed fission neutrons with Cu converter (less efficient but closer to DU sample)
 - + **Irradiated Ge samples** $\sim 500 \text{ n}/\mu\text{m}^2$ (radiation damage)

Active interrogation experiment on Trident

PI: A. Favalli*
LANL



Using laser-driven neutrons to stop nuclear smugglers
LANL press release 6/4/2013




* LANL LDRD Director's Reserve, A. Favalli, PI, Early Career Research

Selected applications enabled by laser-driven ion beams


1. Laser-driven neutron beams

- HED-target probe
- Active interrogation
- Materials science





2. Evolution of high-Z or solid particulates in low-Z plasmas

- Coulomb explosion
- Mix






3. Ion-driven FI

- Laser-driven proton or ion beam ignitor of compressed DT fuel




Important to understand breakup & mixing of particulates in dense low-Z plasmas

- Ubiquitous problem, whether initial state is solid particulates or plasma “blobs”
 - E.g., comet tails, semiconductor manufacturing plasmas, tokamak edge plasmas, ICF & MCF implosions, ...
- May be key to understanding “mix” in dense plasmas
 - E.g., certain laser-fusion capsule ablaters, Magnetized Target Fusion implosions
 - Atomic versus particulate **mix affects TN-burn**
 - 300-fold increase in temperature increases ion classical viscosity $\propto T^{5/2}$ by factor of $\sim 10^6$
 - True viscosity is uncertain, may invalidate our physical picture of compressible hydro mix (BHR*)
 - Electrostatically-enhanced mix** may dominate



Magnetized Target Fusion (MTF)






3D ICF capsule (HYDRA code)

*(Besnard-Harlow-Rauenzahn), D. C. Besnard, F. H. Harlow, and R. M. Rauenzahn, Los Alamos National Laboratory Report No. LA-10911-MS, 1987; A. Banerjee et al., Phys. Rev. E **82**, 046309 (2010)

Mixing across sharp interfaces with heterogeneous species likely dominated by plasma effects


- PIC simulations show multi-species plasma mixing at \sim sonic (ion-sound) speeds, \gg diffusive speeds
 - Electrostatically-enhanced mix** (EEM) requires experimental test
- VPIC simulation of representative case: isobaric, C-D interface



- May dominate “mix” in dense plasmas that affects TN burn
 - Plasma effects can be implemented in mix models like BHR*
- Designed an experiment on Trident to test EEM
 - Use BOA beams to **isochorically heat** a sharp interface


*(Besnard-Harlow-Rauenzahn), D. C. Besnard, F. H. Harlow, and R. M. Rauenzahn, LANL Report No. LA-10911-MS, 1987; A. Banerjee et al., Phys. Rev. E **82**, 046309 (2010)

Experiments on particulate evolution in dense plasmas on the Trident short-pulse laser have been designed.




- Frozen H_2 using technique pioneered by TU Darmstadt or CH foam
- High-Z particulate, wire, foil, $\sim 10 \mu m$

Preliminary data




- Low-Z “background” dense plasma
 - Solid density, $T_e \sim 1 - 20 \text{ eV}$
 - Size $\sim (100 \mu m)^3$
 - Frozen H_2 , CH_2 , ...
 - Heated by a Trident proton beam (ultra-thin CH_2 foils, BOA mechanism) NOT ranging in the sample (known energy deposition)
 - Quasi-homogeneous (simulation)



Selected applications enabled by laser-driven ion beams


1. Laser-driven neutron beams

- HED-target probe
- Active interrogation
- Materials science





2. Evolution of high-Z or solid particulates in low-Z plasmas

- Coulomb explosion
- Mix







3. Ion-driven FI

- Laser-driven proton or ion beam ignitor of compressed DT fuel



FI of DT fuel assembled with long-pulse laser places specific requirements on ion-beam.*

- Ignition HS conditions set by heating & cooling rates¹
- Total ion energy required independent of ion species
- Fuel $\rho r \sim$ particle range \rightarrow laser I_L
 - e^- : ~ 1 MeV $\rightarrow I \sim 5 \times 10^{19}$ W/cm²
 - **Protons: ~ 10 MeV $\rightarrow I_L \sim 10^{20}$ W/cm²**
 - **C: ~ 450 MeV $\rightarrow I_L \sim 10^{21}$ W/cm²**



* E.g., S. Atzeni, et al., *Nuclear Fusion* **42**, L1 (2002); J.C. Fernández, et al., *NF* **49**, 065004 (2009)


¹ S Atzeni S and J Meyer-Ter-Vehn 2004 The physics of inertial fusion (Oxford: Oxford Univ. Press)

² D. Clark & M. Tabak, *Nucl. Fus.* **24**, 1147 (2007)

RPA → BOA ion FI design

Ion FI

VPIC simulation supporting FI design



Review paper submitted to
Nuclear Fusion

LA-UR-12-26959

Fast ignition with laser-driven proton and ion beams

J. C. Fernández¹, B. J. Albright¹, F. N. Beg², M. E. Foord³, B. M. Hegelich¹, J. J. Honrubia⁴, M. Roth⁵, R. B. Stephens⁶, L. Yin¹

¹Los Alamos National Laboratory, Los Alamos, New Mexico, 87544 USA

²University of California-San Diego, La Jolla, California 92093, USA

³Lawrence Livermore National Laboratory, Livermore, California 94551, USA

⁴Universidad Politécnica de Madrid, 28040-Madrid, Spain

⁵Technische Universität Darmstadt, 64289, Darmstadt, Germany

⁶General Atomics, San Diego, California 92121, USA

E-mail: juanc@lanl.gov

Table 4-1: C FI beam parameters using a hybrid RPA-LS – BOA ion acceleration scheme
[1]=Given, from other modeling, [2]=Chosen, [3]=Derived, [4]=From PIC simulation

Parameter	Hybrid	TNSA
E_{ir} [1]	10.5 kJ	12.7 kJ
Ion beam		
	1.1.1.	1.1.2.
Ion species [2]	C	Protons
E_{ki} (ion energy)	400 MeV [2,4]	$T_{\text{h}} = 4$ MeV [1]
δE_{ki} (ion energy spread), $\delta E_{\text{ki}} / E_{\text{ki}}$	50 MeV (~12.5%) [4]	Maxwellian [2]
γ_{i} (ion Relativ. factor), β_{i} (v_{i}/c)	1.0355, 0.256 [3]	1.0043, 0.092 (T_{h})
Target		
Z, A, ρ [g/cm ³] [2]	6, 12, 2.0	29, 63.5, 9.0 + 1.8 μm CH ₂ layer [3]
l (target thickness)	30 nm [2,4]	20 μm [2]
η_{p} (fraction of ions utilized)	0.45 [4]	N.A.
foil travel during t_{L}	5.5 μm [4] ($\ll D_{\text{L}}$)	N.A.
Source-fuel separation d	1 cm	0.5 cm
Laser		
λ_0 (laser wavelength)	1 μm [2]	1.053 μm [2]
Laser polarization	Circular [2]	Linear [2]
a_0, I_{L} (laser intensity)	20, 10^{21} W/cm² [2]	9, 10^{20} W/cm² [1], Ref. [52]
t_{L} (laser pulse length)	11 fs rise time + 126 fs flattop to [4]	1 ps [3]
E_{L} (laser energy)	120 kJ [3]	127 kJ [3]
η_{E} (laser-ion energy efficiency)	0.083 [4]	0.10 (Data in Ref. [52])
$A_{\text{L}}, D_{\text{L}}$ (laser spot area, Diam.)	$1.21 \times 10^{-3} \text{ cm}^2$ (393 μm) [4]	$1.26 \times 10^{-3} \text{ cm}^2$ (400 μm) [2]

Summary

- Many mechanisms for ion acceleration
- Laser-driven ion beams on Trident used for neutron generation
- Laser-driven ion beams to be used on Trident for electrostatically-enhanced mix studies
- Laser-driven ion beams an excellent candidate for FI

